



## COMMERCIAL INSERTION NATURAL

## MATERIAL SPECIFICATION SHEET

PROPERTY	VALUE	UNIT
Elastomer	Natural	
Quality	Commercial Insertion	
Colour	BLACK	
Grade	N66	
Hardness	65	Shore A (+/-5)
Specific Gravity	1.50	g/cm <sup>3</sup>
Tensile Strength	3.5	MPa (Min)
Elongation at Break	300	% (Min)
Tear Strength	12	N/MM
Compression Set	43	%
Working Temperature	-20 to +70	°C

- Has excellent physical properties including abrasion resistance, good tensile strength, low compression set and high tear properties.
- Resistance also to some organic solvents and many organic salts and acids.
- These are good general properties, which will vary between grades.



ISO 9001  
Quality  
Management  
Systems  
CERTIFIED

ISO 14001  
Environmental  
Management  
CERTIFIED

ISO 9001:2015 Q93057

ISO 14001:2015 EMS 505718

The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company