

KLINGERsoft-chem

100% expanded PTFE manufactured to produce a soft, highly compressible gasket material with excellent chemical resistance and good creep properties

The Klinger group has been recognised as the market leader in gaskets and sealing for over a century. Our research and development laboratories have investigated over 250 different fibre forms in the search for asbestos free alternatives. The search has resulted in a range of high quality and high performance asbestos free materials that have been proven in service



BS EN 9100:2003, ISO 9001:2008 Certificate no: FM 1057

General Properties

- Excellent chemical resistance
- High compressibility
- . Good creep resistance
- . Suitable for glass-lined and enamel flanges
- . Seals worn or damaged flanges
- Low bolt load requirement
- Easy to handle and cut
- Suitable for food and pharmaceutical applications

Tests and Certifications

FDA Conformity

Availability Sheeting (m):

1.5 x 1.5

Thickness (mm):

1.0, 1.5, 2.0, 3.0

KLINGER KLINGERsoft-chem 100 90 80 70 3 60 50 DIN 2690/ DIN EN 1514-1 Form IBC bis PN 40* 40 30 1 2 20 bar 'n Л

-200 -150 -100 -50 0°C 50 100 150 200 250 300 350 400

Typical Specifications

Application Guidelines

- 1. Usually satisfactory without reference.
- 2. Usually satisfactory, but suggest you refer to Klinger for advice
- 3. Caution: May be suitable but essential that you refer to Klinger for advice.

Chemical compatibility must be considered in all cases.

Compressibility ASTM F 36 A		60%
Recovery ASTM F 36 A		12%
Stress relaxation DIN 52913	30MPa, 16h/150⁰C	18MPa
Klinger cold/hot compression (25MPa)	Thickness decrease 23ºC	10%
	decrease at 300ºC	40%
Gas leakage according to DIN 3535/6		0.02ml/min
Thickness increase after fluid	HNO ₃ 100%:18h/23 ⁰ C	2-7%
Immersion ASTM F 146	NaOH 33%, 72h/110ºC	12-24%
Density		0.85g/cm ³

Head Office KLINGER Ltd Wharfedale Road Euroway Trading Estate Bradford BD4 6SG

Tel: 01274 688 222 Fax: 01274 688 549 Klinger Ltd. Grangemouth Tel: 01324 472 231 Fax: 01324 482 111 Klinger Ltd. Runcorn Tel: 01928 577 030 Fax: 01928 575 223

Klinger Ltd. Aberdeen Tel: 01224 772 962 Fax: 01224 772 953 Klinger Ltd. Middlesbrough Tel: 01642 220 289 Fax: 01642 220 290

Klinger Ltd. Southampton Tel: 023 8061 1855 Fax: 023 8061 0360

All information and recommendations contained in this specification sheet are to the best of our knowledge correct. Since conditions of use are beyond our control, users must satisfy themselves that the products are suitable for the intended processes and uses. No warranty is given or implied in respect of information or recommendations or that any use of products will not infringe rights belonging to other parties. In any event or occurrence our liability is limited to our invoice value of the goods delivered by us to you. We reserve the right to change product design and properties without notice