

ANSI – ASME- B16.21

N-Bore		Full Face (mm)					ASME B16.21	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 600	OD	ID
0.5	15	95	21	4	16	67		54	21
0.75	20	117	27	4	19	83		67	27
1	25	124	33	4	19	89		73	33
1.25	32	133	42	4	19	98		83	42
1.5	40	156	48	4	22	114		95	48
2	50	165	60	8	19	127		111	60
2.5	65	191	73	8	22	149		130	73
3	80	210	89	8	22	168		149	89
3.5	90	229	102	8	25	184		162	102
4	100	273	114	8	25	216		194	114
5	125	330	141	8	29	267		241	141
6	150	356	168	12	29	292		267	168
8	200	419	219	12	32	349		321	219
10	250	508	273	16	35	432		400	273
12	300	559	324	20	35	489		457	324
14	350	603	356	20	38	527		492	356
16	400	686	406	20	41	603		565	406
18	450	743	457	20	44	654		613	457
20	500	813	508	24	44	724		683	508
24	600	940	610	24	51	838		791	610



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company