



ANSI – ASME- B16.47 A

N-Bore		Full Face (mm)					ASME B16.47 A	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 600	OD	ID
22	550	870	559	24	48	778		733	559
26	650	1016	660	28	51	914		867	660
28	700	1073	711	28	54	965		914	711
30	750	1130	762	28	54	1022		972	762
32	800	1194	813	28	60	1080		1022	813
34	850	1245	864	28	60	1130		1073	864
36	900	1314	914	32	67	1194		1130	914
38	950	1270	965	32	60	1162		1105	965
40	1000	1321	1016	32	60	1213		1156	1016
42	1050	1403	1067	32	67	1283		1219	1067
44	1110	1454	1118	32	67	1334		1270	1118
46	1150	1511	1168	28	67	1391		1327	1168
48	1200	1594	1219	32	73	1461		1391	1219
50	1250	1670	1270	32	79	1524		1448	1270
52	1300	1721	1321	32	79	1575		1499	1321
54	1350	1778	1372	28	79	1632		1556	1372
56	1400	1854	1422	28	86	1695		1613	1422
58	1450	1905	1473	32	86	1746		1664	1473
60	1500	1994	1524	32	92	1810		1721	1524



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company