

## ANSI – ASME- B16.47 B

N-Bore		Full Face (mm)					ASME B16.47 B	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 300	OD	ID
26	650	867	660	32	35	803		772	660
28	700	921	711	36	35	857		826	711
30	750	991	762	36	38	921		886	762
32	800	1054	816	32	41	978		940	816
34	850	1108	864	36	41	1032		994	864
36	900	1172	914	32	44	1089		1048	914
38	950	1222	965	36	44	1140		1099	965
40	1000	1273	1016	40	44	1191		1149	1016
42	1050	1334	1067	36	48	1245		1200	1067
44	1110	1384	1118	40	48	1295		1251	1118
46	1150	1461	1168	36	51	1365		1318	1168
48	1200	1511	1219	40	51	1416		1368	1219
50	1250	1562	1270	44	51	1467		1419	1270
52	1300	1613	1321	48	51	1518		1470	1321
54	1350	1673	1372	48	51	1578		1556	1372
56	1400	1765	1422	36	60	1651		1594	1422
58	1450	1827	1473	40	60	1713		1673	1473
60	1500	1878	1524	40	60	1764		1705	1524



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company