

BS10 STANDARD SIZING

TABLE A

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
0.5	15	95	21	4	14	67	52	21
0.75	20	102	27	4	14	73	59	27
1	25	114	34	4	14	83	68	34
1.25	32	121	43	4	14	87	73	43
1.5	40	133	48	4	14	98	84	48
2	50	153	60	4	18	114	97	60
2.5	65	165	76	4	18	127	110	76
3	80	184	89	4	18	146	129	89
3.5	90	203	102	4	18	165	148	102
4	100	216	114	4	18	178	160	114
5	125	254	140	4	18	210	192	140
6	150	279	168	4	18	235	217	168
7	0	305	194	8	18	260	243	194
8	200	337	219	8	18	292	275	219
9	230	368	244	8	18	324	306	244
10	250	406	273	8	22	356	333	273
12	300	457	324	8	22	406	384	324
13	330	489	356	8	22	438	416	356
14	350	527	381	8	25	470	445	381
15	380	552	406	8	25	495	470	406
16	400	578	432	12	25	521	495	432
17	425	610	457	12	25	552	527	457
18	450	541	483	12	25	584	559	483
19	475	673	508	12	25	610	584	508
20	500	705	533	12	25	641	616	533
21	525	737	559	12	25	673	648	559
22	550	762	584	12	29	699	670	584
23	575	787	610	12	29	724	695	610
24	600	826	635	12	29	756	727	635



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company