

BS10 STANDARD SIZING

TABLE H

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
0.5	15	114	21	4	18	83	65	21
0.75	20	114	27	4	18	83	65	27
1	25	121	34	4	18	87	70	34
1.25	32	133	43	4	18	98	81	43
1.5	40	140	48	4	18	105	86	48
2	50	165	60	4	18	127	110	60
2.5	65	184	76	8	18	146	129	76
3	80	203	89	8	18	165	148	89
3.5	90	216	102	8	18	178	160	102
4	100	229	114	8	18	191	173	114
5	125	279	140	8	22	235	213	140
6	150	305	168	12	22	260	238	168
7	0	337	194	12	22	292	270	194
8	200	368	219	12	22	324	302	219
9	230	406	244	12	25	356	330	244
10	250	432	273	12	25	381	356	273
12	300	489	324	16	25	438	413	324
13	330	527	356	16	29	470	441	356
14	350	552	381	16	29	495	467	381
15	380	578	406	16	29	521	492	406
16	400	610	432	20	29	552	524	432
17	425	641	457	20	29	584	556	457
18	450	673	483	20	32	610	578	483
19	475	705	508	20	32	641	610	508
20	500	737	533	24	32	673	641	533
21	525	762	559	24	32	699	667	559
22	550	787	584	24	32	724	692	584
23	575	826	610	24	35	756	721	610
24	600	851	635	24	35	781	746	635



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company