

## PN40

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	235	115	8	22	190	168	115
5	125	270	141	8	26	220	194	141
6	150	300	169	8	26	250	224	169
8	200	375	220	12	30	320	290	220
10	250	450	274	12	33	385	352	274
12	300	515	325	16	33	450	417	325
14	350	580	356	16	36	510	474	356
16	400	660	407	16	39	585	546	407
18	450	685	458	20	39	610	571	458
20	500	755	508	20	42	670	628	508
24	600	890	610	20	48	795	747	610
28	700	995	710	24	48	900	852	710
32	800	1140	820	24	56	1030	974	820
36	900	1250	910	28	56	1140	1084	910
40	1000	1360	1010	28	56	1250	1194	1010



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company